

TKS-NEBU





TKS-NEBU



Portable unit able to spray the nebulized water up to 7 metres. Ideal for indoor jobs, small and indoor demolitions and renewals. It's also ideal for asbestos removal, sterilization and sanitation

- Compact dimensions
- Easy to handle

STANDARD FEATURES

- Stainless steel 70 litres water tank
- Wheels and handles for transport
- High pressure pump
- Signal for low water level
- Closable for an easy transport
- Manually adjustable nozzles spray angle

OPTIONS

- Connection from the water supply network



Manual **CONTROL PANEL**



REMOTE CONTROL on / off



NOZZLE

TECHNICAL DATA

Water pump	-	230V – 50Hz – 0.55kW – 80 bar	Coverage	m	7 (area 64 sqm)
Nozzles spray angle	-	da 60° a 100°	Dimensions min.	mm	815 x 530 x 1400 h
Tilting angle	-	-20° / 30°	Dimensions max.	mm	815 x 530 x 2200 h
Single phase power	kW	0.6 (230V)	Dimensions satellite min.	mm	20 x 20 x 1200 h
Water tank capacity	l	70	Dimensions satellite max.	mm	60 x 60 x 2100 h
Tank autonomy	hrs	2,30	Dry weight	Kg	120

